

# PostProcess™ CENTI™

## SUPPORT REMOVAL

### AUTOMATED. INTELLIGENT. COMPREHENSIVE.

PostProcess Technologies is the pioneer of the automated post-printing industry. As the first and only provider of automated and intelligent post-print solutions for additive manufacturing, PostProcess increases the consistency, throughput, and productivity of the third step of 3D printing – post-printing.

### PRODUCTION READY.

The PostProcess™ CENTI™ Support Removal solution provides all the conveniences of a compact bench-top footprint, with an envelope sized for a few large or several small geometries. Rely on the patent-pending CENTI for superior support removal for all 3D printed materials, including FDM, SLA, PolyJet, CLIP, and more.

### SOFTWARE DRIVEN.

Paired with our exclusive detergents, the right amount of time, and exact temperature based on the material and geometry of the 3D printed part, the CENTI Production Series Support Removal solution delivers precise, hands-free support removal from 3D printed parts. Utilizing our proprietary software, the CENTI combines multiple forms of customized agitation and optimized energy, and includes:

- Variable temperature (70-156°F)
- Programmable cycle time
- Proprietary *Agitation Algorithms*

#### POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA  
info@postprocess.com +1.866.430.5354

#### POSTPROCESS TECHNOLOGIES INTERNATIONAL

535 Route des Lucioles 06560 Sophia Antipolis, France  
+33 (0)4 22 32 68 13



### HARDWARE FEATURES

- Digital interface
- Piezo-electric Ultrasonics
- Stainless steel envelope
- Removable envelope lid
- Magnetically driven pump

### SIZE & WEIGHT

- Envelope: 19.5" L x 11.5" W x 6" H  
(50 cm x 29 cm x 15 cm)
- Machine footprint: 23.5" L x 18" W x 15.5" H  
(60 cm x 46 cm x 39 cm)
- Volume of parts should not exceed 2/3rds of envelope
- Weight: 35 lbs. empty; 75 lbs. full

### CONSUMABLES

- Capacity: 5 Gallons
- Detergent for Polyjet parts: PG1
- Detergent for SLA & CLIP parts: PG1.2
- Detergent for FDM parts: PG2

### ELECTRICAL

- Voltage: 110V/240V, 60/50Hz
- Amperage: 8.5A/3.9A
- Connector: NEMA 5-15P

### SAFETY FEATURES

- Auto power down
- Compliant with all OSHA regulations
- Noise reducing features for a low dBa