

HARDWARE FEATURES

- Stainless steel envelope
- Counter-weighted vertical sliding door
- In-line strainer
- LED Lighted chamber
- Multiple fixtures available
- Casters for easy installation

RESULTING IN...

- + Superior support removal
- + Evenly treated parts
- + Cycle time reduction

SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- Proprietary *Agitation Algorithms*
- Variable temperature (85-160°F, 29-71°C)
- Intelligent cycle times
- Customizable settings
- One-touch repeatability with recipes storage
- Preventative maintenance schedules

RESULTING IN...

- + Minimized part breakage
- + Minimal operator intervention
- + Preservation of fine-feature details

PRODUCT SPECIFICATIONS

SIZE AND WEIGHT

- Envelope: 19" L x 27.5" W x 26" H
(48 cm x 70 cm x 66 cm)
- Machine Footprint (Closed door):
– 42.25" L x 34.5" W x 84" H
(107 cm x 88 cm x 213 cm)
- Machine Footprint (Open door):
– 95.25" L x 47.5" W x 98.5" H
(243 cm x 121 cm x 250 cm)
- Approx. Weight: 700 lbs. empty, 1000 lbs. full



ELECTRICAL

US:

- Voltage: 208V 3 Phase
- Amperage: 35A
- Connector: 560P9W (IP67)

EU:

- Voltage: 400V 3 Phase
- Amperage: 30A

MATERIALS AND TECHNOLOGIES

- FDM, Polyjet

CONSUMABLES

- Detergent: PG1C for Polyjet
PG2C for FDM

SAFETY FEATURES

- Emergency stop
- Auto-interrupt
- Compliant with all OSHA regulations
- **CE** compliant

POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA
info@postprocess.com +1.866.430.5354

POSTPROCESS TECHNOLOGIES INTERNATIONAL

535 Route des Lucioles 06560 Sophia Antipolis, France
+33 (0)4 22 32 68 13