

## HARDWARE FEATURES

- Stainless steel envelope
- Counter-weighted vertical sliding door
- In-line strainer
- LED Lighted chamber
- Multiple fixtures available
- Casters for easy installation

### **RESULTING IN...**

- + Superior support removal
- + Evenly treated parts
- + Cycle time reduction

## SOFTWARE FEATURES

- Patent-pending AUTOMAT3D<sup>™</sup> platform
- Proprietary *Agitation Algorithms*
- Variable temperature (85-160°F, 29-71°C)
- Intelligent cycle times
- Customizable settings
- One-touch repeatability with recipes storage
- Preventative maintenance schedules

### **RESULTING IN...**

- + Minimized part breakage
- + Minimal operator intervention
- + Preservation of fine-feature details

## PRODUCT SPECIFICATIONS

### **SIZE AND WEIGHT**

- Envelope: 40" L x 27.5" W x 26" H  
(101.5 cm x 69.8cm x 66 cm)
- Machine Footprint (Closed door):  
– 67.5" L x 37" W x 85.25" H  
(172 cm x 94 cm x 217 cm)
- Machine Footprint (Open door):  
– 122.75" L x 83" W x 96.75" H  
(172 cm x 211 cm x 247 cm)
- Approx. Weight: 1500 lbs. empty; 2000 lbs. full



### **ELECTRICAL**

#### **US:**

- Voltage: 208V 3 Phase
- Amperage: 50A
- Connector: HBL560C9W

#### **EU:**

- Voltage: 400V 3 Phase
- Amperage: 25A
- Connector: HBL532P6W

### **MATERIALS AND TECHNOLOGIES**

- FDM, Polyjet

### **CONSUMABLES**

- Detergent: PG1C for Polyjet  
PG2C for FDM
- Anti-Foaming Agent: PG7

### **SAFETY FEATURES**

- Emergency stop
- Auto-interrupt
- Compliant with all OSHA regulations

#### **POSTPROCESS TECHNOLOGIES INC.**

2495 Main Street, Suite 615, Buffalo NY 14214 USA  
info@postprocess.com +1.866.430.5354

#### **POSTPROCESS TECHNOLOGIES INTERNATIONAL**

535 Route des Lucioles 06560 Sophia Antipolis, France  
+33 (0)4 22 32 68 13