

# PostProcess™ **FORTI™** SUPPORT REMOVAL

## SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- Variable temperature (70-158°F, 21-70°C)
- HMI enabled programmable cycle time
- Proprietary *Agitation Algorithms*

## HARDWARE FEATURES

- Piezo-electric ultrasonics
- Stainless steel envelope
- Magnetically driven pump
- Multi-configuration fixture
- Casters for easy installation
- Approximate Weight:  
300 lbs. empty (136 kg);  
470 lbs. full (213 kg)



## PRODUCT SPECIFICATIONS

### SIZE

- Envelope:  
- 13" L x 13" W x 13" H  
(33 cm x 33 cm x 33 cm)
- Machine Footprint:  
- 25" L x 33" W x 42" H  
(63.5 cm x 83.8 cm x 106.6 cm)

### SAFETY FEATURES

- Emergency stop
- Auto power down
- Compliant with all OSHA regulations

### CONSUMABLES

- Capacity: 15 Gallons (56 Liters)
- Detergent: PG1 for Polyjet  
PG1.2 for SLA, CLIP  
PG2 for FDM

### MATERIALS AND TECHNOLOGIES

- FDM, Polyjet, SLA, DLP, CLIP

### ELECTRICAL

#### US

- Voltage: 120V
- Amperage: 20A

#### EU

- Voltage: 230V
- Amperage: 20A



#### POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA  
info@postprocess.com +1.866.430.5354

#### POSTPROCESS TECHNOLOGIES INTERNATIONAL

535 Route des Lucioles 06560 Sophia Antipolis, France  
+33 (0)4 22 32 68 13