

SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- Variable temperature: 86-145°F (30 – 63°C)
- HMI enabled programmable cycle time
- Proprietary *Agitation Algorithms*
- Recipe storage and recall
- Precision control of process parameters
- Preventative maintenance features

HARDWARE FEATURES

- Stainless steel envelope
- Magnetically driven pump
- Multi-configuration fixture
- Casters for easy installation
- Approximate Weight:
300 lbs. empty (136 kg); 470 lbs. full (213 kg)



PRODUCT SPECIFICATIONS

SIZE

- Envelope:
- 14" L x 14" W x 14" H
(35.5 cm x 35.5 cm x 35.5 cm)
- Machine Footprint:
- 29" L x 36" W x 43" H
(73.6 cm x 91.4 cm x 109.2 cm)

ELECTRICAL

NORTH AMERICA FORTI UHP MODEL

- Power: 120V, 60Hz, Connector: NEMA 5-15P
- Dual agitation; includes heater & ultrasonics

FORTI XXP MODEL

- Power: 120V, 60Hz, Connector: NEMA 5-15P

EUROPE

FORTI UHP MODEL

- Power: 230V, 50Hz, Connector: CEE 7/3
- Dual agitation; includes heater & ultrasonics

FORTI XXP MODEL

- Power: 230V, 50Hz, Connector: CEE 7/3

MATERIALS AND TECHNOLOGIES



SLA



DLP



CLIP



FDM



POLYJET

Resin Removal

Support Removal

CONSUMABLES

- Capacity: 17 Gallons (64 Liters)
- Detergent: PLM-101-SUB for Polyjet
PLM-201-SUB for FDM
PLM-403-SUB for SLA, CLIP, DLP

SAFETY FEATURES

- Emergency stop
- Auto power down
- CE 

POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA
info@postprocess.com +1.866.430.5354

POSTPROCESS TECHNOLOGIES INTERNATIONAL

535 Route des Lucioles 06560 Sophia Antipolis, France
+33 (0)4 22 32 68 13